

# TX-22 White

LED-backlit Display

## The Ultimate Interactive Multi-Touch Displays



Featuring an LED-backlit IPS panel, the TX-22 White offers more than just full HD 1920 x 1080 resolution. Consistent and accurate colour is discernible from all viewing angles. Projected capacitive touch technology enables users to navigate the display with ease and precision. Its tilting flexibility ranging from  $-5^{\circ}$  to  $90^{\circ}$  degrees ensures user comfort and ergonomically friendly for public and interactive environments. Glass overlay brings such benefits as ease of cleaning and resistance against water and dust. Durable metal housing and rugged base design guarantee stability as well as strength.





### 10-Point Multi-Touch Display

Integration of 10-point touch and projected capacitive touch technology provides accurate and precise touch experience.



### Maximise User Comfort

With an ergonomically-friendly design, the TX-22 White provides more viewing angles with a wide range tilt flexibility from  $-5^{\circ}$  to  $90^{\circ}$ .



IEC/EN 60601-1  
Medical-Grade

### Medical-Grade Safety Certification

The TX-22 White adopts a specially designed low-voltage medical-grade power supply to ensure safety, performance, and reliability in any professional medical environment. Compliance with the EN/IEC 60601-1 standards ensures their safe and reliable performance in demanding medical settings.

### Complete Protection Against Dust And Water Jets

With the front panel rated IP65, the TX-22 White is effectively protected against the ingress of dust and splashing liquid, a common risk in such demanding public places as hospitals, museums and school labs.



### Features

- Full HD 1920 x 1080 resolution
- IPS Panel technology offers high colour accuracy and wide viewing angles
- NeoV™ Optical Glass helps withstand alcohol and other commonly used cleaning solutions
- Durable metal housing
- EN60601-1 and IEC60601-1 medical certification
- White exterior design for easy contaminant detection
- DC 12V medical-grade power adapter allows a longer distance connection
- Incorporates projected capacitive touch technology
- 10-point simultaneous multi-touch capability
- Windows 10 ready - plug and play support for Windows 7/8/10
- Multi-touch support via driver for Linux and Android OS
- Front-sided IP65 rating protects the screen from liquid and dust
- Lockable OSD settings and control keys to prevent tampering
- Tilt capacity from  $-5^{\circ}$  to  $90^{\circ}$



## Specifications

## TX-22 White

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD (IPS Technology)
	Panel Size	21.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.248 mm
	Brightness	250 cd/m <sup>2</sup>
	Contrast Ratio	1000:1
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7M
	Response Time	5 ms
	Surface Treatment	Anti-Glare Treatment (Haze 25%), 3H Hard Coating
<b>Frequency (H/V)</b>	H Freq.	31 kHz-82 kHz
	V Freq.	50 Hz-75 Hz
<b>Input</b>	DVI	24-Pin DVI-D x 1
	VGA	15-Pin D-Sub x 1
<b>External Control</b>	RJ11	Yes
<b>Touch Screen</b>	Technology	Projective Capacitive
	Positional Accuracy	± 2.5 mm
	Panel Interface	USB (Type-B)
	Multi-touch Plug & Play	10-point touch for Windows 7/8/10
	Single Touch Support by Driver	Windows VISTA/XP/2000/CE/XP Embedded, Mac OS
Multi-touch Support by Driver	Linux (Up to 5 points) Android 2.1 upward and 4.0 as well (Up to 10 points)	
<b>Power</b>	Power Supply	External
	Power Requirements	DC 12V, 4A
	On Mode	19W (On)
	Stand-by Mode	< 2W
Off Mode	< 1W	
<b>Glass</b>	Thickness	3.1 mm (0.12")
	Transmission Rate	> 90%
	Hardness	> 7H
<b>Operating Conditions</b>	Temperature	0°C-40°C (32°F-104°F)
	Humidity	20%-80% (non-condensing)
<b>Storage Conditions</b>	Temperature	-20°C-60°C (-4°F-140°F)
	Humidity	10%-90% (non-condensing)
<b>Mounting</b>	VESA FPM PMI	Yes (100 x 100 mm)
<b>Stand</b>	Tilt	-5° to 90°
<b>Security</b>	Kensington Security Slot	Yes
<b>Dimensions</b>	w/Base (W x H x D)	528.6 x 346.7 x 214.2 mm (20.8" x 13.7" x 8.4")
	Packaging (W x H x D)	610.0 x 460.0 x 320.0 mm (24.0" x 18.1" x 12.6")
<b>Weight</b>	w/Base	6.7 kg (14.8 lb)
	Packaging	9.8 kg (21.6 lb)
<b>Regulation Approval</b>	Certification & Compliance	CE, WEEE, RoHS, REACH, EAC, MDD, EN / IEC 60601-1
<b>Accessories</b>	Supplied	Power Adaptor, Power Cord, VGA Cable, DVI Cable, USB Cable, Warranty Card, CD
<b>Optional Accessories</b>		Wall Mounts: WMK-01, WMK-03, PMK-01

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[displays.agneovo.com](https://displays.agneovo.com)