


QM-Series LED-backlit Display 86" | 75" | 65" | 55" | 43"

Slim Bezel Displays for 4K Signage Solution



The QM-Series 4K slim bezel displays are designed for commercial applications that require crisper and clearer image presentation. Featuring easy-to-use content playback, UHD resolution with a wide viewing angle, the QM-Series displays are ideally designed for retail stores, corporate meeting areas, hotels and other public spaces.





Versatile Connectivity

Easily connect a variety of devices with the versatile connectivity options including DisplayPort*, HDMI, DVI*, VGA, USB, RS232 and RJ45.




Features

- 4K UHD 3840 x 2160 resolution
- Anti-Burn-in™ technology prevents image ghosting
- Durable metal housing (86" and 75" only)
- Image Enhancer: 3D Comb Filter / Noise Reduction / Freeze
- Versatile connectivity: DisplayPort*, HDMI, DVI*, VGA
- Media Playback: play photos, videos and music from a USB drive or micro SD card
- An integrated scheduler allows content programming based on time and day

Experience the 4K Difference

Don't miss a single detail with this powerful 4K display. View smooth 4K video and images with a new level of detail and clarity. Offering 8.3 million pixels, the QM-Series provides the ultimate digital signage experience, delivering business messaging and boost customer engagement.



Simple Content Playback and Scheduling

The embedded media player allows users to conveniently play content from a USB drive or micro SD card. Simply create scheduled playlists based on time and day, and configure playback settings with the included remote control to display your personalized content.

- Alink™ function for synchronized powering on/off via HDMI
- OPS slot for easy digital signage player integration (86", 75" and 65" only)
- RS232/LAN/IR control - provides compatibility with control systems
- Black-level adjustment for presenting more details in dark images
- Selectable gamma curves optimise different kinds of images
- Built-in speakers
- VESA mount compatibility for flexible installation

* Product features may vary by models



Specifications

		QM-86	QM-75
Panel	Panel Type	LED-Backlit TFT LCD (IPS Technology)	LED-Backlit TFT LCD (IPS Technology)
	Panel Size	85.6"	74.5"
	Max. Resolution	UHD 3840 x 2160	UHD 3840 x 2160
	Pixel Pitch	0.494 mm	0.429 mm
	Brightness	410 cd/m ²	410 cd/m ²
	Contrast Ratio	1200:1	1200:1
	Viewing Angle (H/V)	178°/178°	178°/178°
	Display Colour	1.07B	1.07B
	Response Time	5 ms	5 ms
	Surface Treatment	Anti-Glare Treatment (Haze 3%), 2H Hard Coating	Anti-Glare Treatment (Haze 2%), 2H Hard Coating
Frequency (H/V)	H.Freq	31 kHz-92 kHz	31 kHz-92 kHz
	V.Freq	48 Hz-85 Hz	48 Hz-85 Hz
Input	DisplayPort	1.2 x 1	1.2 x 1
	HDMI	2.0 x 4	2.0 x 4
	VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1
External Control	IR in/out	3.5 mm Phone Jack	3.5 mm Phone Jack
	RS232 in/out	2.5 mm Phone Jack	2.5 mm Phone Jack
	LAN (RJ45)	Yes	Yes
Other Connectivity	USB	2.0 x 1 (Service Port / Media Playback) 2.0 x 1 (Media Playback) 3.0 x 1 (Media Playback) USB power outlet x 1 (5V2A)	2.0 x 1 (Service Port / Media Playback) 2.0 x 1 (Media Playback) 3.0 x 1 (Media Playback) USB power outlet x 1 (5V2A)
	OPS Slot	Yes	Yes
	Micro SD Card Slot	Yes	Yes
Audio	Audio In	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
	Audio Out	Stereo Audio Jack (RCA)	Stereo Audio Jack (RCA)
	Internal Speakers	10W x 2	10W x 2
Power	Power Supply	Internal	Internal
	Power Requirements	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
	On Mode	302W (On)	237W (On)
	Stand-by Mode Off Mode	< 0.5W < 0.5W	< 0.5W < 0.5W
Operating Conditions	Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
	Humidity	20%-80% (non-condensing)	20%-80% (non-condensing)
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
	Humidity	10%-90% (non-condensing)	10%-90% (non-condensing)
Mounting	VESA FPMPI	Yes (600 x 400 mm)	Yes (600 x 400 mm)
Dimensions	w/o base (W x H x D)	1927.9 x 1098.9 x 85.9 mm (75.9" x 43.3" x 3.4")	1676.6 x 955.0 x 73.8 mm (66.0" x 37.6" x 2.9")
	Packaging (W x H x D)	2224.0 x 1427.0 x 373.0 mm (87.6" x 56.2" x 14.7")	1832.0 x 1283.0 x 280.0 mm (72.1" x 50.5" x 8.2")
Weight	w/o base	63.8 kg (140.7 lb)	53.0 kg (116.8 lb)
	Packaging	93.0 kg (205.0 lb)	65.5 kg (144.4 lb)
Regulation Approval	Certifications & Compliance	CE, CB, FCC, RoHS, WEEE, REACH, EAC	CB, CE, FCC, RoHS, WEEE, REACH, EAC
Accessories	Supplied	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, Quick Start Guide	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, Quick Start Guide
Optional Accessories		Video Wall Mounts: VWM-01, VWM-02 Wall Mounts (Landscape only): LMK-01, LMK-03 Floor Mounts (Landscape only): FMC-03 + LMK-04, FMC-04 + LMK-04	Video Wall Mounts: VWM-01, VWM-02 Ceiling Mount (Landscape only): CMP-01 + LMK-01 Wall Mounts (Landscape only): LMK-01, LMK-03 Floor Mounts (Landscape only): FMC-03 + LMK-04, FMC-04 + LMK-04



Specifications

		QM-65	QM-55	QM-43
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Disply Colour Response Time Surface Treatment	LED-Backlit TFT LCD (VA Technology) 64.5" UHD 3840 x 2160 0.372 mm 350 cd/m ² 4000:1 178°/178° 1.07B 5 ms Anti-Glare Treatment (Haze 2%), 3H Hard Coating	LED-Backlit TFT LCD (VA Technology) 54.6" UHD 3840 x 2160 0.315 mm 350 cd/m ² 4000:1 178°/178° 1.07B 5 ms Anti-Glare Treatment (Haze 2%), 3H Hard Coating	LED-Backlit TFT LCD (VA Technology) 42.5" UHD 3840 x 2160 0.245 mm 350 cd/m ² 5000:1 176°/176° 1.07B 5 ms Haze 2%
Frequency (H/V)	H.Freq V.Freq	31 kHz-92 kHz 48 Hz-85 Hz	31 kHz-92 kHz 48 Hz-85 Hz	31 kHz-92 kHz 48 Hz-85 Hz
Input	DisplayPort HDMI DVI VGA	1.2 x 1 2.0 x 4 - 15-Pin D-Sub x 1	- 2.0 x 2 2 15-Pin D-Sub x 1	- 2.0 x 2 2 15-Pin D-Sub x 1
External Control	IR in/out RS232 in/out LAN (RJ45)	3.5 mm Phone Jack 2.5 mm Phone Jack Yes	3.5 mm Phone Jack 2.5 mm Phone Jack Yes	3.5 mm Phone Jack 2.5 mm Phone Jack Yes
Other Connectivity	USB OPS Slot Micro SD Card Slot	2.0 x 1 (Service Port / Media Playback) 2.0 x 1 (Media Playback) 3.0 x 1 (Media Playback) USB power outlet x 1 (5V2A) Yes Yes	2.0 x 1 (Service Port / Media Playback) 3.0 x 1 (Media Playback) - Yes	2.0 x 1 (Service Port / Media Playback) 3.0 x 1 (Media Playback) - Yes
Audio	Audio In Audio Out Internal Speakers	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) 10W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) 10W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) 10W x 2
Power	Power Supply Power Requirements On Mode Stand-by Mode Off Mode	Internal AC 100-240V, 50/60 Hz 186W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 145W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 110W (On) < 0.5W < 0.5W
Operating Conditions	Temperature Humidity	0°C-40°C (32°F-104°F) 20%-80% (non-condensing)	5°C-40°C (41°F-104°F) 20%-80% (non-condensing)	5°C-40°C (41°F-104°F) 20%-80% (non-condensing)
Storage Conditions	Temperature Humidity	-20°C-60°C (-4°F-140°F) 10%-90% (non-condensing)	-20°C-60°C (-4°F-140°F) 10%-90% (non-condensing)	-20°C-60°C (-4°F-140°F) 10%-90% (non-condensing)
Mounting	VESA FPMPMI	Yes (400 x 400 mm)	Yes (400 x 400 mm & 400 x 200 mm)	Yes (400 x 400 mm & 200 x 200 mm)
Security	Kensington Security Slot	Yes	Yes	Yes
Dimensions	w/o base (W x H x D) Packaging (W x H x D)	1458.7 x 834.7 x 81.6 mm (57.4" x 32.9" x 3.2") 1655.0 x 1078.0 x 280.0 mm (65.2" x 42.4" x 8.2")	1239.2 x 711.6 x 61.7 mm (48.8" x 28.1" x 2.4") 1366.0 x 864.0 x 185.0 mm (53.7" x 34.0" x 7.3")	968.2 x 559.4 x 59.9 mm (38.1" x 22.0" x 2.4") 1070.0 x 696.0 x 159.0 mm (42.1" x 27.4" x 6.3")
Weight	w/o base Packaging	24.8 kg (54.7 lb) 35.2 kg (77.6 lb)	16.0 kg (35.3 lb) 23.0 kg (50.7 lb)	8.7 kg (19.2 lb) 12.2 kg (26.9 lb)
Regulation Approval	Certifications & Compliance	CB, CE, FCC, RoHS, WEEE, REACH, EAC	CB, CE, FCC, BSMI, RoHS, WEEE, REACH, EAC	CB, CE, FCC, RoHS, WEEE, REACH, EAC
Accessories	Supplied	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, Quick Start Guide	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, Quick Start Guide	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, Quick Start Guide
Optional Accessories		Video Wall Mounts: VWM-01, VWM-02 Stand: STD-08 Ceiling Mounts (Landscape only): CMP-01 + LMK-01 Wall Mounts (Landscape only): LMA-01, LMK-01, LMK-03 Floor Mounts (Landscape only): FMS-01, FMS-02, FMC-02, FMC-03 + LMK-04, FMC-04 + LMK-04	Video Wall Mounts: VWM-01, VWM-02 Stand: STD-07 Ceiling Mounts (Landscape only): CMP-01 + LMK-01, CMP-01 + LMK-02, CMP-01 + WMK-03 Wall Mounts (Landscape only): LMA-01, LMK-01, LMK-02, LMK-03 Floor Mounts (Landscape only): FMS-01, FMS-02, FMC-02, FMC-03 + LMK-04, FMC-04 + LMK-04	Video Wall Mounts: VWM-01, VWM-02 Stand: STD-07 Ceiling Mounts (Landscape only): CMP-01 + LMK-01, CMP-01 + LMK-02, CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, LMA-01, LMK-01, LMK-02, LMK-03, WMK-03 Floor Mounts (Landscape only): FMS-01, FMS-02, FMC-02